

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the present application:

Listing of Claims:

- 1-7. (Canceled).
8. (Previously Presented) In a wireless communication system, a method comprising:
 - estimating a channel condition over a first time window;
 - comparing the estimated channel condition to a first threshold value;
 - determining a transmission rate for transmission of quality messages and differential indicators based on the comparison;
 - transmitting quality messages at the transmission rate; and
 - transmitting differential indicators independently of quality messages.
9. (Original) The method as in claim 8, wherein the first time window is dynamically adjusted based on operation of the system.
10. (Original) The method as in claim 8, further comprising:
 - calculating an average channel condition; and
 - calculating variance of the channel condition.
11. (Previously Presented) A wireless apparatus, comprising:
 - means for estimating a channel condition over a first time window;
 - means for comparing the estimated channel condition to a first threshold value;
 - means for determining a transmission rate for transmission of quality messages and differential indicators based on the comparison;
 - means for transmitting quality messages at the transmission rate; and

means for transmitting differential indicators independently of quality messages.

12. (Original) In a wireless communication system for processing voice communications and packet-switched communications, a base station comprising:

receive circuitry operative to receive signals on a reverse link, including a quality message with a parity check, and differential indicators, the quality message periodically providing a quality metric of a forward link, wherein the differential indicators track the quality metric between successive quality messages;

a memory storage unit operative to store a quality message received on the reverse link; and

a differential analyzer to update the quality message stored in the memory storage unit in response to the differential indicators and the parity check.

13. (Previously Presented) A wireless apparatus, comprising:

processing unit, operative for executing computer-readable instructions; and

a memory storage unit adapted to store a plurality of computer-readable instructions for:

generating quality messages and differential indicators at a first frequency, the quality messages providing information on the quality of a communication link, wherein the differential indicators track a quality metric between successive quality messages; and

generating a parity check for each of the quality messages.

14. (Original) The apparatus of claim 13, wherein the plurality of computer-readable instructions are further adapted for:

generating differential indicators at a second frequency, the differential indicators indicating changes in the quality of the communication link, wherein the second frequency is greater than the first frequency.

15. (Previously Presented) A wireless apparatus, comprising:
- processing unit, operative for executing computer-readable instructions; and
 - a memory storage unit adapted to store a plurality of computer-readable instructions for:
 - estimating a channel condition over a first time window;
 - comparing the estimated channel condition to a first threshold value;
 - determining a transmission rate for transmission of quality messages and differential indicators based on the comparison;
 - transmitting quality messages at the transmission rate; and
 - transmitting differential indicators independently of quality messages.
16. (Previously Presented) In a wireless communication system, the wireless communication system supporting a plurality of carriers, a method comprising:
- determining an average channel condition among the plurality of carriers;
 - comparing the average channel condition to a first threshold value;
 - determining a transmission rate for transmission of quality messages and differential indicators based on the comparison;
 - transmitting quality messages at the transmission rate; and
 - transmitting differential indicators independently of quality messages.
17. (Original) The method as in claim 16, further comprising:
- assigning a weight to each of the plurality of carriers, wherein the average channel condition is a weighted average.
18. (Previously Presented) A wireless apparatus, comprising:
- processing unit, operative for executing computer-readable instructions; and

a memory storage unit adapted to store a plurality of computer-readable instructions for:

determining a best channel condition associated with a first frequency; and
generating a quality message, the quality message including a quality indicator and a frequency indicator, the frequency indicator identifying the first frequency; and
generating differential indicators separately from the quality message.

19. (Original) The wireless apparatus as in claim 18, wherein the frequency indicator is a pointer to select the first frequency from a plurality of predetermined frequencies.
20. (New) A wireless apparatus, comprising::
 - a quality measurement unit configured to estimate a channel condition over a first time window;
 - a differential analyzer configured to compare the estimated channel condition to a first threshold value; and
 - a controller configured to determine a transmission rate for transmission of quality messages and differential indicators based on the comparison, the differential analyzer further configured to generate quality messages at the transmission rate, the differential analyzer further configured to transmit differential indicators independently of quality messages.
21. (New) The wireless apparatus of claim 20, wherein the first time window is dynamically adjusted based on operation of the system.
22. (New) The method as in claim 8, wherein the controller is figured configured to:
 - calculate an average channel condition; and
 - calculate a variance of the channel condition.